



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

SECTION 1. IDENTIFICATION

Product name : SynPower™ Synthetic SAE 75W-140 Limited Slip Gear Oil

Product code : VV982

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

Recommended use of the chemical and restrictions on use

Recommended use : Engine, gear & lubricating oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitisation : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing mist or vapours.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	>= 10 - <= 30
Polysulfides, di-tert-Bu	68937-96-2*	>= 3 - <= 7
Mineral Oil - mixture	-	>= 1 - <= 5
Phosphoric acid esters, amine salt	-	>= 1 - <= 5

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and : No symptoms known or expected.
May cause an allergic skin reaction.



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

delayed
Notes to physician : No hazards which require special first aid measures.
Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.



SAFETY DATA SHEET
 SynPower™ Synthetic SAE 75W-140 Limited
 Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

- Advice on safe handling : Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Hand protection
- Material : neoprene, nitrile rubber
 - Break through time : >= 240 min
 - Glove thickness : >= 0.35 mm
 - Guideline : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

		<p>EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.</p> <p>The suitability for a specific workplace should be discussed with the producers of the protective gloves.</p>
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	288.5 °F / 142.5 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower	:	No data available



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

flammability limit

Vapour pressure : No data available

Relative vapour density : > 1
AIR=1

Relative density : No data available

Density : ca. 0.8603 g/cm³ (60.1 °F / 15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 171 mm²/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : excessive heat
Exposure to air or moisture over prolonged periods.

Incompatible materials : Aldehydes
Amines
Bases
Copper
Copper alloys
halogens
Oxidizing agents
peroxides
strong mineral acids
strong reducing agents

Hazardous decomposition products : No hazardous decomposition products are known.



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Polysulfides, di-tert-Bu:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Polysulfides, di-tert-Bu:

Result : Mild skin irritation

Phosphoric acid esters, amine salt:

Result : Mild skin irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The toxicological data has been taken from products of similar composition.

Polysulfides, di-tert-Bu:

Result : Slight, transient irritation

Phosphoric acid esters, amine salt:

Result : Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

Polysulfides, di-tert-Bu:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Polysulfides, di-tert-Bu:

Genotoxicity in vitro : Test Type: in vitro assay
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Cell type: Bone marrow
Method: OECD Test Guideline 474



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Mineral Oil - mixture:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Mineral Oil - mixture:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Polysulfides, di-tert-Bu:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Mineral Oil - mixture:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Phosphoric acid esters, amine salt:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Harmful to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

Persistence and degradability

Components:

Polysulfides, di-tert-Bu:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 13 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methanol	67-56-1	100	100 (F003)
ethylbenzene	100-41-4	100	100 (F003)
4-methylpentan-2-one	108-10-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCOMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

ethylbenzene	100-41-4	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

ethylbenzene	100-41-4	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified 64742-55-8

Pennsylvania Right To Know

PROPRIETARY OF 000000238545	Not Assigned
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
branched hexatriacontane	151006-62-1
1-Dodecene, homopolymer, hydrogenated	151006-63-2
DIALKYL CARBOXYLATE	Not Assigned
Polysulfides, di-tert-Bu	68937-96-2
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified	64742-52-5

Maine Chemicals of High Concern

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0
ethylbenzene	100-41-4
naphthalene	91-20-3

Vermont Chemicals of High Concern

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0
ethylbenzene	100-41-4
naphthalene	91-20-3

Washington Chemicals of High Concern

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0
ethylbenzene	100-41-4
naphthalene	91-20-3

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	On the inventory, or in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1
Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -



SAFETY DATA SHEET
SynPower™ Synthetic SAE 75W-140 Limited
Slip Gear Oil

Version: 4.1

Revision Date: 04/08/2025

Print Date:
01/07/2026

Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/08/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0388288